











| | SMALL 16'-25' 4.87 m-7.62 m | | | | | |
|-----------------------------------|---|--|--|---|--|--|
| MIL-SPEC SHELTERS | UNIVERSAL VESTIBULE | HGPTS | DYNAMIC | MULTI-PURPOSE AREA, Type II (BEAR KITCHEN) | MULTI-PURPOSE AREA, Type I (BEAR KITCHEN) | ACE Adaptive Color and Energy Shelter |
| SERIES SKU | C28 | C14 | C22 | C27 | C27 | C29 |
| NSN | Pending | 8340-01-535-6379 (Tan) | 8340-01-721-4172 (Tan) 8340-01-721-4164 (Green) | 5410-01-626-8713 (Tan) | 5410-01-626-8712 (Tan) | Pending |
| DIMENSIONS | 6' x 6' 1.83 m x 1.83 m | 16' x 16' 4.88 m x 4.88 m | 20' x 32.5' 6.10 m x 9.91 m | 20'4" x 80' 6.20 m x 24.39 m | 40' x 80' 12.2 m x 24.39 m | 19'5" x 33' 5.92 m x 10.05 m |
| SUPPORT SYSTEM | Frame | Frame | Frame | Frame | Frame | Frame |
| RIDGE (APEX) HEIGHT* | 7' 2.14 m | 11' 3.36 m | 10' 3.05 m | 12'11" 3.70 m | 12'11" 3.70 m | 11'8" 3.56 m |
| EAVE HEIGHT* | 6'8" 2.03 m | 7' 2.14 m | N/A | 7'1" 2.17 m | 7'1" 2.17 m | 7'4" 2.24 m |
| TOTAL INTERIOR SQUARE FOOTAGE | 36 ft ² 3.34 m ² | 256 ft ² 23.8 m ² | 640 ft ² 59.5 m ² | 1,600 ft ² 148.7 m ² | 3,200 ft ² 297.3 m ² | 606 ft ² 56.3 m ² |
| TOTAL WEIGHT UNPACKED | 205 lbs 92.99 kg | 570 lbs 258.6 kg | 1,200 lbs 544.4 kg | 11,000 lbs 4,989.6 kg | 24,000 lbs 10,886.3 kg | 1,512 lbs 685.8 kg |
| SET UP TIME/ NUMBER OF PERSONS | 2 People 10 minutes (Under canopy 1 Person 2 minutes or less) | 4 People 30 minutes | 4 People 30 minutes | 6 People 7 hours | 6 People 12 hours | 6 people 40 minutes |
| SNOW LOAD** | 20 psf 97.65 kg/m | 10 psf 48.82 kg/m ² | 20 psf 97.65 kg/m ² | 10 psf 48.82 kg/m ² | 10 psf 48.82 kg/m ² | 20 psf 97.65 kg/m ² |
| WIND LOAD** | 90 mph 144.9 kph | 55 mph 88.6 kph | 90 mph 144.9 kph | 90 mph 144.9 kph | 90 mph 144.9 kph | 90 mph 144.9 kph |
| RAIN LOAD | 2"/5.08 cm per hour with 55 mph/88.51 kph winds | 4"/10.16 cm per hour | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 2"/5.08 cm per hour with 55 mph/88.51 kph winds |







CELINA offers a range of shelter accessories including standard thermal flies, vestibules, corridors, a variety of doors, lighting, flooring, generators, and ECU's. Most shelters can be constructed at any length by adding/removing bays.
* Increased ridge and eave height options available on some models. **Increased snow and wind load options available on some models.





| | MEDIUM 25'-50' 7.62 m-15.24 m | LARGE 50'+ 15.24 m + | | | |
|-----------------------------------|--|---|---|--|--|
| MIL-SPEC SHELTERS | DYNAMIC  | DOME   | | UAV LAMS (UNMANNED AERIAL VEHICLE)   | |
| | SERIES SKU | C26 | C30 | C30 | C23 |
| NSN | 8340-01-721-4150 (Tan) 8340-01-721-4139 (Green) | 5410-01-455-2004 (Tan) | 5410-01-494-5130 (Tan) | 8340-01-721-4062 (Tan) 8340-01-721-4045 (Green) | 8340-01-721-4108 (Tan) 8340-01-721-4101 (Green) |
| DIMENSIONS | 30' x 52' 9.16 m x 15.85 m | 69'5" x 89'3" 21.19 m x 27.22 m | 69'5" x 116'3" 21.19 m x 35.45 m | 83' x 142' 25.30 m x 43.29 m | 83' x 164' 25.3 m x 49.99 m |
| SUPPORT SYSTEM | Frame | Frame | Frame | Frame | Frame |
| RIDGE (APEX) HEIGHT* | 15' 4.58 m | 25' 7.62 m | 25' 7.62 m | 27'9" 8.52 m | 27'9" 8.52 m |
| EAVE HEIGHT* | N/A | 11' 3.36 m | 11' 3.36 m | 10' 3.05 m | 10' 3.05 m |
| TOTAL INTERIOR SQUARE FOOTAGE | 1,500 ft ² 139.4 m ² | 5,300 ft ² 492.4 m ² | 8,000 ft ² 743.3 m ² | 11,010 ft ² 10,22.9 m ² | 12,055 ft ² 1,120 m ² |
| TOTAL WEIGHT UNPACKED | 3,460 lbs 1,569.5 kg | 21,220 lbs 9,625.2 kg | 28,210 lbs 12,795.8 kg | 25,000 lbs 11,339.9 kg | 26,000 lbs 11,793.5 kg |
| SET UP TIME/ NUMBER OF PERSONS | 6 People 3 hours | Max 6 Persons 144 man hours or less | Max 8 Persons 256 man hours or less | Max 8 Persons 576 man hours or less | Max 8 Persons 576 man hours or less |
| SNOW LOAD** | 16 psf 78.12 kg/m ² | 20 psf 97.65 kg/m ² | 20 psf 97.65 kg/m ² | 15 psf 73.24 kg/m ² with snow load cables | 15 psf 73.24 kg/m ² with snow load cables |
| WIND LOAD** | 90 mph 144.9 kph | 105 mph 168.9 kph | 105 mph 169 kph | 90-115 mph 144.9-185.1 kph | 90-115 mph 144.9-185.1 kph |
| RAIN LOAD | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds |



| | LARGE 50'+ 15.24 m + | | | | |
|---------------------------------------|---|---|--|--|--|
| MIL-SPEC SHELTERS | MLAMS (MODULAR) | | | | |
| | A (AVIATION)  | A (AVIATION)  | V (VEHICLE)  | V (VEHICLE)  | S (STORAGE)  |
| SERIES SKU | C23 | C23 | C23 | C23 | C23 |
| NSN | 5410-01-724-2703 (Tan and Green) | 8340-01-707-9507 (Tan) | 5410-01-724-4085 (Tan and Green) | 8340-01-808-9546 (Tan) | Pending |
| DIMENSIONS | 75' x 192' 22.89 m x 58.52 m | 75' x 195' 22.89 m x 59.44 m | 75' x 128' 22.89 m x 39 m | 75' x 132' 22.89 m x 40.24 m | 52' x 63' 15.85 m x 19.20 m |
| SUPPORT SYSTEM | Frame | Frame | Frame | Frame | Frame |
| RIDGE (APEX) HEIGHT* | 31' 9.45 m | 31' 9.45 m | 31' 9.45 m | 31'/33'* 9.45 m / 10.06 m* | 25'5" 7.78 m |
| EAVE HEIGHT* | 16' 4.88 m | 16' 4.88 m | 16' 4.88 m | 16'/18'* 4.88 m / 5.49 m* | 16' 4.88 m |
| TOTAL INTERIOR SQUARE FOOTAGE | 12,998 ft ² 1207.6 m ² | 14,400 ft ² 1,337.8 m ² | 8,363 ft ² 777 m ² | 8,450 ft ² 785.9 m ² | 3,276 ft ² 304.4 m ² |
| TOTAL WEIGHT UNPACKED | 26,597 lbs 12,064.2 kg | 28,000 lbs 12,700.6 kg | 18,750 lbs 8,504.8 kg | 20,265 lbs 9,192.1 kg | 11,535 lbs 5232.2 kg |
| SET UP TIME/ NUMBER OF PERSONS | Max 8 Persons 576 man hours or less | Max 8 Persons 576 man hours or less | Max 8 Persons 384 man hours or less | Max 8 Persons 384 man hours or less | Max 8 Persons 192 man hours or less |
| SNOW LOAD** | 8 psf 39.06 kg/m ² without snow struts | 8 psf 39.06 kg/m ² without snow struts | 8 psf 39.06 kg/m ² without snow struts | 8 psf 39.06 kg/m ² without snow struts | 8 psf 39.06 kg/m ² without snow struts |
| WIND LOAD** | 90-115 mph 144.9-185.1 kph | 90-115 mph 144.9-185.1 kph | 90-115 mph 144.9-185.1 kph | 90-115 mph/ 144.9-185.1 kph** 135 mph/ 217.3 kph** | 90-115 mph 144.9-185.1 kph |
| RAIN LOAD | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds |

| SHIPPING CONTAINER OPTIONS | 20' | 40' | BICON | TRICON | QUADCON | 463L |
|----------------------------|---|---|---|---|---|---|
| |  |  |  |  |  |  |

| | LARGE 50'+ 15.24 m + | |
|-----------------------------------|---|---|
| MIL-SPEC SHELTERS | CELINA LAMS | CTO LAMS (CONFIGURE TO ORDER) |
| | (STORAGE) | CTO (VEHICLE) |
| |  |  |
| SERIES SKU | C23 | C23 |
| NSN | 8340-01-721-3551 (Tan) 8340-01-721-3526 (Green) | Pending |
| DIMENSIONS | 52' x 50' 15.85 m x 15.24 m | 75' x 122' 22.89 m x 37.19 m |
| SUPPORT SYSTEM | Frame | Frame |
| RIDGE (APEX) HEIGHT* | 25'5" 7.78 m | 31' 9.45 m |
| EAVE HEIGHT* | 16' 4.88 m | 16' 4.88 m |
| TOTAL INTERIOR SQUARE FOOTAGE | 2,600 ft ² 241.6 m ² | 8,500 ft ² 789.7 m ² |
| TOTAL WEIGHT UNPACKED | 10,285 lbs 4,665.2 kg | 20,000 lbs 9,071.8 kg |
| SET UP TIME/ NUMBER OF PERSONS | Max 8 Persons 192 man hours or less | Max 8 Persons 384 man hours or less |
| SNOW LOAD** | 8 psf 39.06 kg/m ² without snow struts | 8 psf 39.06 kg/m ² without snow struts |
| WIND LOAD** | 90-115 mph 144.9-185.1 kph | 90-115 mph 144.9-185.1 kph |
| RAIN LOAD | 4"/10.16 cm per hour with 40 mph/64.38 kph winds | 4"/10.16 cm per hour with 40 mph/64.38 kph winds |

