## PRODUCT DATA SHEET

Part #: C23083X164TT-T • NSN: 8340-01-721-4108









## CELINA LARGE AREA MAINTENANCE SHELTER (LAMS) UAV-83'x 164'-TAN

**CONTRACTOR NAME:** CELINA Tent, Inc.

1. PART NUMBER: C23083X164TT-T 2. NSN: 8340-01-721-4108

5. CLASS: 12165 3. NAME: CELINA Large Area Maintenance 4. TYPE: Frame Structure, Expandable Shelter LAMS, UAV

7. SUPPORT SYSTEM: Frame 6. COLOR: Tan 8. SERIES: C23

9. INTENDED USE: Maintenance Shelter: Aviation, Vehicle, Storage

**HEIGHT: RIDGE: 27'9" EAVE: 10'** 10. DIMENSIONS (IN FEET AND INCHES): **LENGTH:** 164' **WIDTH: 83'** 

11. DIMENSIONS (EXTERNAL GUYED): **LENGTH: 164' WIDTH: 93'** 

12. SQUARE FEET INTERIOR: 12,055 sq. ft.

13. WEIGHT (POUNDS, UNPACKAGED): 14. WEIGHT (PACKAGED): 15. SHIPPING CUBE (PACKAGED): 26,000 lbs

39,425 lbs 3.870 Cubic Feet

LENGTH: 20'-0"/40'-0" 16. SHIPPING CONTAINER: (1) 20' ISO Con-WIDTH: 8'-0"/8'-0" HEIGHT: 8'-6"/9'-6"

tainer and (1) 40' ISO High Cube Container

17. SET-UP TIME/NUMBER OF PERSONS: 18. STRIKE TIME/NUMBER OF PERSONS: Max 8 Persons/576 man hours or less Max 8 Persons/432 man hours or less

#### 19. PARTS INCLUDED (Include Quantity):

(1) Aluminum Frame with (2) Full-width Tri-Lid Doors (1) Fabric Cover Kit, (2) Personnel Doors (Composite, Single), (1) LAMS Electrical/ Lighting Kit (8-LED Lights / 16-outlets / 1-Panel Box), (2) Ventilators (External/Electric), (1) LAMS Installation tool kit, (1) 20' ISO Shipping Container, (1) 40' ISO High Cube Shipping Container

#### 20. DESCRIPTION:

CELINA's 83' x 164' Large Area Maintenance Shelter (LAMS), Type UAV/Drone, includes two retractable Tri-lid Doors, allowing for full-width entries when in the open state and protection from environmental elements when in the closed state. This shelter also includes vehicle and personnel side doors, allowing for easy access. CELINA's LAMS are designed for various uses, including maintenance space, general purpose, general storage, training space, and aircraft hangars. This expeditionary shelter design is completely mobile and relocatable, and can be deployed on any ground type. Pre-assembled hardware allows for quick shelter installation. Meets general requirements from US Military specifications MIL-PRF-32504B (MLAMS) (2AUG2016). CELINA's LAMS are Berry Compliant.



MADE IN THE USA · BERRY AMENDMENT COMPLIANT

# **PRODUCT DATA SHEET**

Part #: C23083X164TT-T • NSN: 8340-01-721-4108



| 21. ACCESSORY AND SUPPORT EQUIPMENT:           |                                  |                       |  |
|--|----------------------------------|-----------------------|--|
|  | PART NUMBER OR NSN:              | INCLUDED OR OPTIONAL: | DESCRIPTION:   |
| LIGHT SET<br>Product Data Sheet                | LAMSELEC4LTWW                    | INCLUDED              | Included in LAMS Electrical Kit (8-LED Lights/16-Outlets)                                      |
| ELECTRICAL OUTLET SET<br>Product Data Sheet    |                                  | INCLUDED              |  |
| FLOORING<br>Product Data Sheet                 |                                  | OPTIONAL              | Call for additional flooring options   |
| HEATER<br>Product Data Sheet                   | 34456-50 (50hz)<br>34456 (60hz)  | OPTIONAL              | ECU Assembly, 10-Ton, 50hz, Skid Mounted, Tan<br>ECU Assembly, 10-Ton, 60hz, Skid Mounted, Tan |
| AIR CONDITIONER<br>Product Data Sheet          |                                  |                       |  |
| GENERATOR<br>Product Data Sheet                |                                  | OPTIONAL              | Call for additional generator options  |
| POWER DISTRIBUTION<br>Product Data Sheet       | LAMSELEC4LTWW                    | INCLUDED              | Included in LAMS Electrical Kit (1-Panel Box)  |
| INSULATED LINER<br>Product Data Sheet          | L23083X164INS                    | OPTIONAL              | Standard Insulated Liner Kit for L218 - 83'x164' - 10' Eaves                                   |
| STANDARD LINER<br>Product Data Sheet           | L23083X164                       | OPTIONAL              | Standard Liner Kit for L218 - 83'x164' - 10' Eaves   |
| INSULATED FLOORING<br>Product Data Sheet       |                                  | OPTIONAL              | Call for additional flooring options   |
| 22. SNOW LOAD:<br>15 psf with snow load cables | <b>23. WIND LOAD:</b> 90-115 mph |                       | 24. RAIN LOAD:<br>4" per hour with 40 MPH Winds  |





### **Professional Engineer Stamp**

