

PRODUCT DATA SHEET

Part#: C23052X050GG-G • NSN:8340-01-721-3526



CELINA LARGE AREA MAINTENANCE SHELTER (LAMS) -52'x50' -GREEN

CONTRACTOR NAME: CELINA Tent, Inc.

| | | | |
|--|--|--|--|
| 1. PART NUMBER: C23052X050GG-G | | 2. NSN: 8340-01-721-3526 | |
| 3. NAME: CELINA LAMS, 52' x 50', Green | 4. TYPE: Large Area Maintenance Shelter LAMS/ MLAMS | | 5. CLASS: 02762 |
| 6. COLOR: Green | 7. SUPPORT SYSTEM: Frame | | 8. SERIES: C23 |
| 9. INTENDED USE: Maintenance Shelter: Vehicle, Storage | | | |
| 10. DIMENSIONS (IN FEET AND INCHES): | | LENGTH: 50' | WIDTH: 52' |
| | | HEIGHT: RIDGE: 25'5" EAVE: 16' | |
| 11. DIMENSIONS (EXTERNAL GUYED): | | LENGTH: 50' | WIDTH: 62' |
| 12. SQUARE FEET INTERIOR: 2,600 sq. ft. | | | |
| 13. WEIGHT (POUNDS, UNPACKAGED): 10,285 lbs | | 14. WEIGHT (PACKAGED): 14,935 lbs | 15. SHIPPING CUBE (PACKAGED): 2,720 Cubic Feet |
| 16. SHIPPING CONTAINER: (1) 20' ISO Container | LENGTH: 20'-0" | WIDTH: 8'-0" | HEIGHT: 8'-6" |
| 17. SET-UP TIME/NUMBER OF PERSONS: Max 8 Persons/192 man hours or less | | 18. STRIKE TIME/NUMBER OF PERSONS: Max 8 Persons/144 man hours or less | |

19. PARTS INCLUDED (Include Quantity):

(1) Aluminum Frame with (2) Gable End Walls, (1) Fabric Cover Kit, (2) Personnel Doors (Composite, Single), (1) LAMS Electrical/Lighting Kit (4-LED Lights / 8-outlets / 1-Panel Box), (1) Ventilator (External/Electric), (1) LAMS Installation tool kit, (1) 20' ISO Shipping Container

20. DESCRIPTION:

CELINA's 52' x 50' Large Area Maintenance Shelter (LAMS) is compliant with MIL-PRF-32504B (MLAMS) (2AUG2016). Each end of the shelter has gable end wall with sliding fabric doors. This shelter also includes personnel side doors, allowing for easy access. CELINA's LAMS are designed for various uses, including maintenance space, general purpose, general storage, training space, and aircraft hangars. This expeditionary shelter design is completely mobile and relocatable, and can be deployed on any ground type. Pre-assembled hardware allows for quick shelter installation. CELINA's LAMS are Berry Compliant.



MADE IN THE USA • BERRY AMENDMENT COMPLIANT

PRODUCT DATA SHEET

Part#: C23052X050GG-G • NSN:8340-01-721-3526



21. ACCESSORY AND SUPPORT EQUIPMENT:

| | PART NUMBER OR NSN: | INCLUDED OR OPTIONAL: | DESCRIPTION: |
|---|---------------------------------|---|--|
| LIGHT SET Product Data Sheet | E2304LT60 | INCLUDED | Included in LAMS Electrical Kit (4-LED Lights/8-Outlets) |
| ELECTRICAL OUTLET SET Product Data Sheet | | INCLUDED | |
| FLOORING Product Data Sheet | | OPTIONAL | Call for additional flooring options |
| HEATER Product Data Sheet | 34456-50 (50hz) 34456 (60hz) | OPTIONAL | ECU Assembly, 10-Ton, 50hz, Skid Mounted, Tan ECU Assembly, 10-Ton, 60hz, Skid Mounted, Tan |
| AIR CONDITIONER Product Data Sheet | | | |
| GENERATOR Product Data Sheet | | OPTIONAL | Call for additional generator options |
| POWER DISTRIBUTION Product Data Sheet | E2304LT60 | INCLUDED | Included in LAMS Electrical Kit (1-Panel Box) |
| INSULATED LINER Product Data Sheet | L23052X050INS | OPTIONAL | Standard Insulated Liner Kit for L218 - 52'x50' - 16' Eaves |
| STANDARD LINER Product Data Sheet | L23052X050 | OPTIONAL | Standard Liner Kit for L218 - 52'x50' - 16' Eaves |
| INSULATED FLOORING Product Data Sheet | | OPTIONAL | Call for additional flooring options |
| 22. SNOW LOAD: 8 PSF | 23. WIND LOAD: 90 MPH | 24. RAIN LOAD: 4" per hour with 40 MPH Winds | |



Professional Engineer Stamp

